
# The Biggest Thing in Big LCD Monitors

## LCD-2007HDL







### Active Matrix 20" Color LCD Monitor

#### • HD compatible (supports 480p/i, 576p/i, 720p, 1080i)

- · Component input capability provides superior viewing pleasure
- Aspect ratio: 16:9
- Anti-glare hard coating covers glass surface
- Zoom function
- · Wireless remote control
- · Dual built-in front speakers for easy listening
- · For color and B&W applications
- Low power consumption
- · Case made of durable black ABS plastic
- · Active matrix technology allows wide viewing angle
- · Active matrix technology eliminates distortion
- Switching power supply (AC 90~240V, 50 ~ 60Hz) included
- · Built-in removable desk stand included
- Built-in interface and proper cable exiting for wall or arm mounting VESA 100mm FPMPMI compliant
- Response Time: 8ms/8ms (rising/falling)

**Resolution: 1366 (H) x 768 (V) dots** 

Brightness rating: 450 cd/m<sup>2</sup> (Nit)

Contrast Ratio: 700:1

Display: 20" TFT LCD active matrix

Back Light: Built-in CCFTs

Input Signal: Composite NTSC/PAL (auto sensing for video)

S-Video, component, Analog RGB

Colors: 16.7 M Number of Pixels: 480.000 dots

Viewing angle L/R/T/B: 80/80/70/70 degrees

Pixel Configuration: Stripe

Video Input Level: 1.0V p-p at 75 Ohm

Audio Input:  $400 \pm 50 \text{mV}$  (rms) at 1 KHz Stereo

Audio Output: 1V P-P

Built-in Speakers: 3 W/ channel x 2

Dimensions w/ desk stand (WHD): 554.8 x 433 x 160mm / 21.8" x 17" x 6.3" Dimensions w/o desk stand (WHD): 554.8 x 401 x 80mm / 21.8" x 15" x 2.75"

Actual visible screen size (WH):  $408 \times 306 mm / 16" \times 12"$ Operating temperature:  $50 \sim 104$ °F or  $10 \sim 40$ °C Storage temperature:  $-4 \sim 140$ °F or  $-20 \sim 60$ °C

Power Requirement: 100 ~ 240VAC, 50/60Hz, 12 VDC, 7A, negative ground

Power Consumption: 80 W (max)

Connectors: RCA A/V IN jacks, S-Video

RCA YPbPr inputs and RCA R/L audio inputs

15-pin D-sub, PC audio IN

Threaded "F" connector for LCD-2007HDT

2.1mm DC IN jack

Net weight: 5 kg. / 11 lbs. Gross weight: 6.4 kg. / 14 lbs.

#### **Optional Accessories**

HM-400 Under-cabinet hinge mount (shown below)

WM-31 Wall mount bracket (fixed)

WM-302 Wall mount with swing arm & 4-way (shown below)

WMC-1720 Ceiling mount

Specifications subject to change without notice

60

©2008 ToteVision

Available through: